



SIMATIC S7-200, CPU 221 COMPACT UNIT, AC POWER SUPPLY
6 DI DC/4 DO RELAY 4 KB CODE/2 KB DATA,

Figure similar

Supply voltage

Rated value (AC)

- | | |
|------------|-----|
| • 120 V AC | Yes |
| • 230 V AC | Yes |

Load voltage L+

- | | |
|---------------------------------------|------|
| • Rated value (DC) | 24 V |
| • permissible range, lower limit (DC) | 5 V |
| • permissible range, upper limit (DC) | 30 V |

Load voltage L1

- | | |
|--|-----------------------------|
| • Rated value (AC) | 100 V; 100 V AC to 230 V AC |
| • permissible range, lower limit (AC) | 5 V |
| • permissible range, upper limit (AC) | 250 V |
| • permissible frequency range, lower limit | 47 Hz |
| • permissible frequency range, upper limit | 63 Hz |

Input current

- | | |
|------------------------------|---|
| Inrush current, max. | 20 A; at 264 V |
| from supply voltage L1, max. | 120 mA; 15 to 60 mA (240 V); 30 to 120 mA (120 V); output current for expansion modules (5 V DC) 340 mA |

Encoder supply

24 V encoder supply

- | | |
|----------------------------|--|
| • 24 V | Yes; Permissible range: 20.4V to 28.8V |
| • short-circuit protection | Yes; electronic at 600 mA |
| • Output current, max. | 180 mA |

Memory

Number of memory modules (optional)	1; pluggable memory module, content identical with integral EEPROM; can additionally store recipes, data logs and other files
Work memory	
• integrated (for program)	4 kbyte
• integrated (for data)	2 kbyte
Backup	
• present	Yes; Program: Entire program maintenance-free on integral EEPROM, programmable via CPU; data: Entire DB 1 loaded from PG/PC maintenance-free on integral EEPROM, current values of DB 1 in RAM, retentive memory bits, timers, counters, etc. maintenance-free via high-performance capacitor; optional battery for long-term buffering
Battery	
Backup battery	
• Backup time, max.	50 h; (min. 8 h at 40 °C); 200 days (typ.) with optional battery module
CPU processing times	
for bit operations, max.	0.22 µs
Counters, timers and their retentivity	
S7 counter	
• Number	256
of which retentive with battery	
— can be set	Yes; via high-performance capacitor or battery
— lower limit	1
— upper limit	256
Counting range	
— lower limit	0
— upper limit	32 767
S7 times	
• Number	256
of which retentive with battery	
— can be set	Yes; via high-performance capacitor or battery
— upper limit	64
Time range	
— lower limit	1 ms
— upper limit	54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min
Data areas and their retentivity	
Flag	
• Number, max.	32 byte
• Retentivity available	Yes; M 0.0 to M 31.7
• of which retentive with battery	0 to 255, via high-performance capacitor or battery, adjustable

- of which retentive without battery

0 to 112 in EEPROM, adjustable

Hardware configuration

connectable programming devices/PCs

SIMATIC PG/PC, standard PC

Digital inputs

Number of digital inputs

6; Integrated

m/p-reading

Yes; optionally, per group

Input voltage

- Rated value (DC)
- for signal "0"
- for signal "1"

24 V

0 to 5 V

min. 15 V

Input current

- for signal "1", typ.

2.5 mA

Input delay (for rated value of input voltage)

for standard inputs

— Parameterizable

Yes; all

— at "0" to "1", min.

0.2 ms

— at "0" to "1", max.

12.8 ms

for interrupt inputs

— Parameterizable

Yes; I 0.0 to I 0.3

for counter/technological functions

— Parameterizable

Yes; (E 0.0 to E 0.5) 30 kHz

Cable length

- shielded, max.
- unshielded, max.

500 m; Standard input: 500 m, high-speed counters: 50 m

300 m; not for high-speed signals

Digital outputs

Number of digital outputs

4; Relays

short-circuit protection

No; to be provided externally

Switching capacity of the outputs

- with resistive load, max.
- on lamp load, max.

2 A

30 W with DC, 200 W with AC

Output voltage

- for signal "1", min.

L+/L1

Output current

- for signal "1" rated value
- for signal "0" residual current, max.

2 A

0 mA

Output delay with resistive load

- "0" to "1", max.
- "1" to "0", max.

10 ms; all outputs

10 ms; all outputs

Parallel switching of 2 outputs

- for uprating

No

Total current of the outputs (per group)

all mounting positions	
— up to 40 °C, max.	6 A
horizontal installation	
— up to 55 °C, max.	6 A
Relay outputs	
• Number of relay outputs, integrated	4
• Number of operating cycles, max.	10 000 000; mechanically 10 million, at rated load voltage 100,000
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Analog inputs	
Number of analog potentiometers	1; Analog potentiometer; resolution 8 bit
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Functionality	
• MPI	Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
• PPI	Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s
• serial data exchange	Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbit/s; the PC/PPI cable can also be used as RS232/RS485 converter
MPI	
• Transmission rate, min.	19.2 kbit/s
• Transmission rate, max.	187.5 kbit/s
Integrated Functions	
Number of counters	4; High-speed counters (30 kHz each), 32 bits (incl. sign), can be used as up/down counters or for connecting 2 incremental encoders with 2 pulse trains offset by 90° (max. 20 kHz (A/B counters)); parameterizable enable and reset input; interrupt facilities (incl. call of subroutine with any content) when the setpoint is reached; reversal in counting direction, etc.
Counting frequency (counter) max.	30 kHz

Number of alarm inputs	4; 4 rising edges and/or 4 falling edges
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> • between the channels 	Yes
<ul style="list-style-type: none"> • between the channels, in groups of 	2 and 4
Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels 	Yes; Relays
<ul style="list-style-type: none"> • between the channels, in groups of 	1 and 3
Permissible potential difference	
between different circuits	500 V DC between 24 V DC and 5 V DC; 1500 V AC between 24 V DC and 230 V AC
Degree and class of protection	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes
Ambient conditions	
Environmental conditions	For further environmental conditions, see "Automation System S7-200, System Manual"
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. 	0 °C
<ul style="list-style-type: none"> • horizontal installation, max. 	55 °C
<ul style="list-style-type: none"> • vertical installation, min. 	0 °C
<ul style="list-style-type: none"> • vertical installation, max. 	45 °C
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> • permissible range, min. 	860 hPa
<ul style="list-style-type: none"> • permissible range, max. 	1 080 hPa
Relative humidity	
<ul style="list-style-type: none"> • Operation, min. 	5 %
<ul style="list-style-type: none"> • Operation, max. 	95 %; RH class 2 in accordance with IEC 1131-2
Configuration	
Programming	
<ul style="list-style-type: none"> • Command set 	Bit logic instructions, compare instructions, timer instructions, counter instructions, clock instructions, transmissions instructions, table instructions, logic instructions, shift and rotate instructions, conversion instructions, program control instructions, interrupt and communications instructions, logic stack instructions, integer maths, floating-point math instructions, numerical functions
<ul style="list-style-type: none"> • Program processing 	free cycle (OB 1), interrupt-controller, time-controlled (1 to 255 ms)
<ul style="list-style-type: none"> • Program organization 	1 OB, 1 DB, 1 SDB subroutines with/without parameter transfer
<ul style="list-style-type: none"> • Number of subroutines, max. 	64
Programming language	

— LAD	Yes
— FBD	Yes
— STL	Yes

Know-how protection

• User program protection/password protection	Yes; 3-stage password protection
---	----------------------------------

Connection method

Plug-in I/O terminals	No
-----------------------	----

Dimensions

Width	90 mm
Height	80 mm
Depth	62 mm

Weights

Weight, approx.	310 g
-----------------	-------

last modified: 10.06.2015